

TCL SOLAR

T Class Solar Panel

Product: HSM-ND66-GK

700-725 W | Up to 23.3% efficient

 Ideal for power plant applications

 Framed glass-glass

 Bifacial energy generation



High energy yield

- Consistent energy production across all weather conditions
- Bifacial energy generation

Elegant design

- Sleek panel aesthetic
- High-durability frame and heat-strengthened glass

Reliable operation

- Rigorous supply chain qualification procedures
- Easy to install
- Backed by a bankable company

Comprehensive warranty coverage

Product and power coverage

15-30 Years

Year 1 minimum warranted output

99.0%

Maximum annual degradation

0.40%

TCL SOLAR

Learn more about TCL Solar panels
www.tclsolar.com/resources



T CLASS POWER: 700-725 W | EFFICIENCY: Up to 23.3%

Electrical Data, Front STC Characteristics ¹					
	HSM-ND66-GK725	HSM-ND66-GK720	HSM-ND66-GK715	HSM-ND66-GK710	HSM-ND66-GK705
Nominal Power (Pnom) ²	725 W	720 W	715 W	710 W	705 W
Power Binning	3/0%	3/0%	3/0%	3/0%	3/0%
Panel Efficiency	23.3%	23.2%	23.0%	22.9%	22.5%
Rated Voltage (Vmpp)	41.27 V	41.08 V	40.89 V	40.69 V	40.50 V
Rated Current (Impp)	17.57 A	17.53 A	17.49 A	17.45 A	17.41 A
Open-Circuit Voltage (Voc) ²	49.36 V	49.14 V	48.92 V	48.70 V	48.48 V
Short-Circuit Current (Isc) ²	18.60 A	18.56 A	18.52 A	18.48 A	18.44 A


BNPI Data ³					
Nominal Power (Pmax) ²	801 W	795 W	790 W	784 W	779 W
Open-Circuit Voltage (Voc) ²	49.52 V	49.29 V	49.08 V	48.85 V	48.64 V
Short-Circuit Current (Isc) ²	20.54 A	20.49 A	20.45 A	20.40 A	20.36 A

Bifacial Gain ⁴					
Pmax with 5% Bifacial Gain	761 W	756 W	751 W	746 W	740 W
Isc with 5% Bifacial Gain	19.53 A	19.49 A	19.45 A	19.40 A	19.36 A
Pmax with 10% Bifacial Gain	798 W	792 W	787 W	781 W	776 W
Isc with 10% Bifacial Gain	20.46 A	20.42 A	20.37 A	20.33 A	20.28 A
					20.24 A

Electrical Data		Mechanical Data	
Bifaciality ($\phi P_{max}/\phi I_{sc}$)	80% +/-5%	Solar Cells	N-Type TOPCon
Bifaciality (ϕV_{oc})	98% +/-2%	Glass	2.0 mm + 2.0 mm, high transmission heat strengthened glass, AR coating on front glass
Maximum System Voltage	1500 V IEC	Junction Box	IP-68, 3 bypass diodes
Testing Temperature	-40°C to +85°C	Connector	Stäubli MC4-EVO2A
Operation Temperature	-40°C to +70°C (IEC TS 63126)	Weight	38.2 kg
Maximum Series Fuse	35 A	Max. Load ⁵	Wind: 2400 Pa, 245 kg/m ² front & back Snow: 5400 Pa, 550 kg/m ² front
Power Temp. Coef.	-0.28% / °C	Impact Resistance	25 mm diameter hail at 23 m/s
Voltage Temp. Coef.	-0.24% / °C	Frame	Anodized Aluminum Alloy
Current Temp. Coef.	0.045% / °C		

Packaging Configuration	
Number of modules per pallet	33
Number of pallets per 40ft HQ container	18
Number of modules per container	594

Tests And Certifications	
Standard Tests	IEC 61215, IEC 61730
Fire Rating	Class A (IEC 61730-2 / UL 790)
Protection Class	Class II (IEC 61140)
Quality Certs	ISO 9001:2015, ISO 14001:2015
EHS Compliance	ISO 45001-2018, Recycling Scheme



Please read the safety and installation instructions.
Visit www.tclsolar.com/resources
Paper version can be requested through
techsupport.EN@sunpowerglobal.com

1 Standard Test Conditions (1000 W/m² irradiance, AM 1.5, 25° C).
NREL calibration Standard: SOMS current, LACCS FF and Voltage.
2 Measurements tolerance +/-2%.

3 BNPI Test Condition (front 1000 W/m², rear 135 W/m² irradiance, AM 1.5, 25° C).

4 The additional gain from the back side of the panel compared to the power of the front side of the panel at the standard test conditions. It depends on mounting (structure, height, tilt angle etc.) and albedo of the underlying surface.

5 Test load as per IEC 61215-2 is equal to design load with safety factor = 1.5. See "Safety and Installation Instructions" for details.

Specifications included in this datasheet are subject to change without notice.
©2025 TCL SunPower Global. All Rights Reserved.

TCL SOLAR

554574 REV A / A4_EN
Publication Date: Dec. 2025